


# The Perfect Fit for Wherever You Work

The compact and versatile ECOSYS PA2100cwx is the ultimate blend of productivity, high-quality and reliability, making it the ideal A4 printer for smaller workgroups or remote workspaces.



**ECOSYS PA2100cwx**



**Up to 22 pages per minute**

**Flexible media support**

**Standard Wireless Printing**

**Mobile Print compatibility**

**BASIC SPECIFICATIONS**

**Configuration:** KYOCERA ECOSYS® Colour Network Printer  
**Pages Per Minute:**  
**Black** – Letter: 22 ppm, Legal: 18 ppm, A4: 21 ppm  
**Colour** – Letter: 22 ppm, Legal: 18 ppm, A4: 21 ppm  
**Warm Up Time:** 32 Seconds or Less (Power On), 12 Seconds or Less from Sleep  
**First Page Out:**  
**Print:** 11 Seconds or Less Black, 12.5 Seconds or Less Colour<sup>1</sup>  
**Display:** 2 Line LCD  
**Resolution:** 600 x 600 dpi, 9600 dpi equivalent x 600 dpi, 1200 x 1200 dpi<sup>2</sup>  
**Memory:** Standard 512MB  
**Duplex:** Standard Stackless Duplex Supports Statement to Legal (5.5" x 8.5" – 8.5" x 14"), 16 – 32 lb Bond (60 – 120gsm)  
**Dimensions / Weight:** 16.2" W x 16.2" D x 12.9" H / 46.3 lbs  
**Maximum Monthly Duty Cycle:** 65,000 Pages per Month

**POWER CONSUMPTION**

**Electrical Requirements:** 120V, 60Hz, 8.6A; 220 – 240V, 50/60Hz, 4.5A  
**Typical Electricity Consumption (TEC):** 120V: 763 Wh/week; 220 – 240V: 691 Wh/week  
**Maximum (including options):** 120V: 985 W; 220 – 240V: 1,052 W  
**Printing:** 120V: 345 W; 220 – 240V: 345 W  
**Ready Mode:** 120V: 33 W; 220 – 240V: 33 W  
**Sleep Mode:** 120V: 0.9 W; 220 – 240V: 0.9 W  
**Power Off:** 120V: 0.2 W; 220 – 240V: 0.2 W

**PRINT SPECIFICATIONS**

**Standard Controller:** Cortex-A9 / 800MHz  
**PDLs / Emulations:** PRESCRIBE, PCL6 (PCL5c/PCL-XL), KPDL3 Supporting AES, PDF Direct Print, XPS/OpenXPS Direct Print  
**Fonts:** 93 Scalable Fonts for PCL6, 93 Fonts for KPDL3, 8 Fonts for Windows Vista, 1 Bitmap Font  
**Windows OS Compatibility:** Windows 8.1/10/11 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019  
**Mac OS Compatibility:** Apple Macintosh OS X 10.9 or higher  
**Interfaces:** Standard: 10 BASE-T/100 BASE-TX / 1000 BASE-T, High-speed USB 2.0, 1 USB Host, Wireless LAN IEEE 802.11b/g/n, Wi-Fi Direct

**Linux OS**

**Mobile Printing:** Apple AirPrint®, KYOCERA Mobile Print, Mopria®  
**Network Protocols:** TCP/IP, IPv4, IPv6, NetBEUI, FTP, LPR, IPP, WSD Print, DHCP, DNS, Apple Bonjour, SNMP v2/3, HTTP, SMTP, POP3, PDF Direct Print (using KYOCERA NET Direct Print utilities)  
**Drivers:** KX Driver, KX (XPS) Driver, PCL Mini Driver, KPDL Mini Driver, MAC Driver, Linux Driver  
**Utilities:** KYOCERA Net Direct Print, File Management Utility, KYOCERA Mobile Print, KYOCERA Print Center, KYOCERA Net Viewer, ID Register, Wi-Fi Setup Tool, Remote Work Assistant, Status Monitor  
**Job Management:** 20 Department Codes  
**Additional Print Features:** EcoPrint, Private Print, Proof and Hold; Quick Copy2 and Job Storage<sup>2</sup>

**SECURITY SPECIFICATIONS**

**Standard:** Network Authentication, IPsec, SNMPv3, LDAP over SSL, IEEE 802.1x, IPP over SSL/TLS, HTTPS, SMTP, POP3 over SSL/TLS, Enhanced WSD over SSL/TLS, TLS 1.2, SMBv3, SHA-2 384  
**Optional:** Card Authentication Kit (B)

**PAPER SUPPLY**

**Standard Paper Sources:** Single 250 Sheet Drawer, 50 Sheet Multi-purpose Tray  
**Standard / Maximum Paper Sources:** 2/3 including Multi-purpose Tray  
**Standard / Maximum Paper Capacity:** 300 Sheets/550 Sheets  
**Paper Size:** Standard / Optional / MPT Drawers: 5.5" x 8.5" – 8.5" x 14" (Statement to Legal)  
**Paper Weight:** Standard / Optional Drawers: 16 lb Bond – 90 lb Index (60 – 163gsm); MPT: 16 lb Bond – 120 lb Index (60 – 220gsm)  
**Input Materials:** Standard / Optional Drawer: Plain Paper, Bond Paper, Recycled Paper; MPT: Labels, OHP, Envelopes, Coated Paper

**PAPER HANDLING OPTION**

**PF-5110:** 250 Sheet Paper Feed Drawer  
**Paper Size / Weight:** 5.5" x 8.5" – 8.5" x 14" (Statement to Legal) / 16 lb Bond – 90 lb Index (60 – 163gsm)  
**Dimensions / Weight:** 16.1" W x 17.6" D x 5.5" H / 8 lbs.

**ADDITIONAL OPTIONS**

**SD Card:** 16 / 32GB  
**Security:** Card Authentication Kit (B)  
**Print Management:** ThinPrint (UG-33)

**Note:**  
<sup>1</sup> At reduced speed  
<sup>2</sup> Requires optional SD Card

Specifications and design are subject to change without notice. For the latest on connectivity visit [kyoceradocumentsolutions.us](http://kyoceradocumentsolutions.us). ECOSYS, PRESCRIBE, Kyocera Net Manager, Kyocera Net Viewer, Kyocera Device Manager, PDF Direct Print, Command Center RX, and KX Driver are trademarks of The Kyocera Companies. Mac OS and AirPrint are trademarks of Apple, Inc. Windows is a trademark of Microsoft, Inc. All other trademarks are the property of their respective owners.



Kyocera Document Solutions Partner

KYOCERA Document Solutions Canada, Ltd.  
 6120 Kestrel Road, Mississauga,  
 ON L5T 1S8, Canada  
 Tel: 905-670-4425



[kyoceradocumentsolutions.ca](http://kyoceradocumentsolutions.ca)